



Application: Condensate Pump; suitable for use with condensate from high efficiency condensing furnaces and boilers

Dimensions: 12"L X 7"W X 6"H

Lift: 22'

Features: Vibration dampening feet and motor mounts, four inlet holes, clear indicator display, float switch and check valve, pan pull dispenser

Part Number

CP-22



Application: ClearVue™ Condensate Pump; provides variable speed and lift; suitable for use with condensate from high efficiency condensing furnaces and boilers

Dimensions: 11.8"L X 5.9"W X 6.7"H

Lift: Variable up to 22'

Features: Floatless sensor, self cleaning, half gallon tank capacity, 4' remote shutoff leads with insulated terminals, polyethelene inlet covers (2)

Part Number

IQP-22



Application: Wet Switch Flood Detector; designed to detect the presence of condensate water overflow

Features: Hydrophillic pad, epoxy encapsulated Solid State electronics, double throw relay, multi-unit connectivity, stainless steel sensor array

Part Number

WS-1



Application: SwitchCap™ Multiple Valve Capacitor; provides two easily switchable capacitors in one

Features: Easy-to-set switches (no jump wires), non-conductive polymer enclosure, multiple opening voltages, wide ambient temperature range, hermetically sealed, UL certified

Part Number

SCAP-60D



Application: Charles Gallo Brand Drain Gun; designed to blow out drain lines instantly

Features: Uses 1200 PSI of oil free/food grade CO₂ (no need for air or nitrogen), flexible hose assembly, tapered fittings work on 3/8" to 3/4" drain openings, portable design

Part Number

GG-1



Application: SWOOSH Cartridges; refill cartridges for the Charles Gallo Brand Drain Gun (GG-1)

Features: Oil-free/food-grade CO₂ (no need for air or nitrogen), environmentally safe and recyclable, 12 cartridges per package

Part Number

GGC-12